

IMPORTANT !!!

For the maximal efectivity of the charge proces is necessary to have the power between the elektrods MINIMALY 40 mA.

If it isn't, it's mostly because the new water hasn't enough minerals and so smal electric conductivity. Solution is very easy - to put to the pool water NaCl (kooking salt) ones on the biggining only, 1kg / 10 cbm.

TIMES FOR FILTER UNIT DURING THE STARTING PROCES:

POOL: 15-40m3	4 hours / daily	
40-70m3	5 -,-	
80-100m3	6 -,-	FOR BIGGER POOLS YOU CAN USE
100-130m3	8 -,-	MORE AMUR SYSTEMS !!!
130-160m3	10 -,-	<u>This one is to the capacity 200 m3 !!!</u>
160-200m3	12 -,-	

AMUR operating unit after „starting proces“

Position 1 till 15m3	pos.2 till 30m3	pos.3 till 40m3
Pos 4 50m3	5 70m3	6 100m3
Pos 7 130m3	8 160m3	9 200m3

The free ionts will stay in the pool water, it means, is necessary to adjust a new filled water only ! (after back wash atc.)

During 7-10 days is necessary to check , eventually adjust pH of pool water. Once per month check the quantity of cupper free ionts. If the capacity is between 0,2 - 0,3 mg / liter, everything is OK. If not, move with the button on the operating unit to the next position up or down. If is too much, you can this unit switch off. (about your experiences).

As soon as you will change all water in the pool, the start proces must be repeated from the biggining !

The elektrods will decreased and about the pool capacity are for 3 – 5 year.

The cleaning of the elektrods during starting proces each 1 week, after this one, 1 per month. For the cleaning you can use soft mechanical method with fine glas paper.